

## ROCKCOTE 2MM TROWEL ON

Active From:

11 Jan 2024

Rockcote 2mm Trowel On is a flexible acrylic based coating that uses pebbles to create a unique patterned finish. Rockcote 2mm Trowel On is normally finished in a traditional travertine style (vertical strike lines), but can also be swirl finished.

Overcoating with Rockcote Armour is recommended.

### Features

- Water based
- Ease of use
- Vapour permeable

### Benefits

- Tough
- Flexible
- Excellent adhesion
- Long term exterior protection

### Uses

- Suitable to go over properly primed and prepared substrates such as brick, block, cement render, Rockcote render, concrete, cement sheeting, AAC panels/blocks and plasterboard.
- Can be used interior and exterior.
- Can be over coated with Rockcote Repel or Rockcote Clearcote or Rockcote Armour/Flex for added durability and lower maintenance.

### Colours and Gloss

- Can be tinted to a wide range of colours achieving a natural finish.
- Available in light base only.

**Sheen Level:**

Matt

**Coverage Rate:**

9m<sup>2</sup>/15ltr

Coverage rates may vary according to substrate and preparation. Theoretical coverage is approx 9 square metres per 15 litre drum.

**Application Method:**

Trowel, then Polystyrene Float

**Dry Film Build:**

2mm

### Typical Data at 25°C and 50% Relative Humidity

**Drying Time:** 24 hours

**Touch Dry:** 5 hours

**Dry to Coat:** 24 hours

**No of Coats:**

1

**Clean Up:**

Water

**Packaging Sizes:**

15L

**Thinning:**

Up to 5%

**Abrasion Resistance:**

Excellent

### Substrate Conditions

- Rockcote 2mm Trowel On must be applied over properly prepared substrates that are free of dirt, dust, grime and any other contaminants.
- Substrates must not contain more than 15% moisture prior to or during application.
- Do not apply if air and surface temperatures are below 5°C or above 35°C.
- If applying over Rockcote Quick Render, application may proceed after 48 hours if properly cured.
- Fresh cementitious substrates such as site mix sand and cement render and concrete must be left for up to 28 days to sufficiently cure prior to application of Rockcote 2mm Trowel On.
- Rockcote Anti Efflorescent Primer should be used when applying over site mix render.

## ROCKCOTE 2MM TROWEL ON

Active From:

11 Jan 2024

### Application

- Check colour before use.
- Ensure same batch numbers are used on a single wall where possible.
- Mix to help reactivate and aerate contents.
- Apply evenly over the properly prepared substrate with a hawk and trowel.
- Ideally apply slightly thicker than the sand granules to achieve optimum results.
- Rockcote 2mm Trowel On is normally finished with a polystyrene float.
- Be sure to keep a wet edge with this product and plan your work to suit the product and weather conditions.
- If joining up to previous day's application, it is "good working practice" to start and finish on an external or internal corner.
- Keep sheltered from rain and moisture for 24-48 hours after completion dependent on climatic conditions.
- If a coloured topcoat will not be used, it is advisable to apply a primer that is tinted to the required finish colour before the application of Rockcote 2mm Trowel On.

### Precautions and Limits

- Check colour before use.
- Ensure same batch numbers are used on a single wall where possible.
- Should not be applied in temperatures below 5°C or above 35°C.
- Not suitable for areas of continual damp or areas submerged in water.

### Transport and Storage

- Store in a cool dark place
- Keep pail sealed
- Do not stack over 3 high

### Disposal

- Dispose of in accordance with local council regulations

### Safety Data

Refer to Rockcote 2mm Trowel On SDS.

### Disclaimer

Rockcote Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, Rockcote Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.