

Technical Data Sheet

ROCKCOTE ACRYBOND

Effective From 21 Apr, 2022

ROCKCOTE Acrybond is an acrylic bonding agent designed to be added to ROCKCOTE Quick Render Grey and Off-White to increase adhesion and strength. ROCKCOTE Acrybond is also suitable to be used as a primer to reduce suction over highly absorbent substrates such as AAC panel.

Features

- Easy to use
- Excellent adhesion properties

Benefits

- Will provide a stronger and harder render, when used as an additive to ROCKCOTE Quick Render Grey and Off-White *Please refer to ROCKCOTE Quick Render TDS.
- ROCKCOTE Acrybond is suitable to be used as a primer to reduce suction over highly absorbent substrates such as AAC panel.

Uses

- Adding to cement based render
- Priming high suction substrates

Colours and Gloss N/A
Sheen Level N/A

Coverage Rate 12-15m²/ltr
Application Method Roller brush or spray
Dry Film Build 7-10 microns
Wet Film Build 40 microns

Typical Data at 25°C and 50% Relative Humidity

Drying Time 4 hours
Touch Dry 30 minutes
Dry to Recoat 2 hours

Usual No Coats

Clean Up Water

Packaging Sizes Trade 20L 15L 10L 4L 1L

Volume Solids 47

Thinning Can be thinned when used as a primer

Elongation Rate

Crack Bridging

Abrasion Resistance

Moisture Control Excellent

Water Resistance Excellent

Pot Life

Substrate Conditions

- Must be applied over properly prepared substrates that are free of dirt, dust and any other contaminants
- All substrates must be installed as per manufacturers' specifications prior to application

Technical Data Sheet

ROCKCOTE ACRYBOND

Effective From	21 Apr, 2022
-----------------------	--------------

Application

- When adding to ROCKCOTE Quick Render, add 10% ROCKCOTE Acrybond to gauging water
- When using as a primer over AAC, mix with equal parts of water

Precautions and Limitations

- Only to be used for specified purpose

Transport and Storage

- Store in a dark cool place
- Keep drum sealed
- Do not stack over 2 high

Disposal

- Dispose of in accordance with local council regulations

Safety Data

Refer to ROCKCOTE Acrybond SDS

Disclaimer

Rockcote Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, Rockcote Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.