

Rockcote Clay Plaster Decor (Dry)

Active From:

23 Jul 2026

Rockcote Clay Plaster Décor is a truly beautiful fine finishing clay plaster with built-in marble dust that glistens in the presence of ambient light. An earthen-look plaster with a smooth finish, Rockcote Clay Plaster Décor adds textural warmth to the interior of any building - from a traditional straw bale home to the most elegant modern building.



Features

- Can be used to achieve a range of specialist finishes and textures.
- Zero VOC. Ideal for people conscious about their health and the health of their families.
- Allows surfaces to breathe, contributing to improved indoor air quality.
- Ability to create textural depth in a smooth, flat surface.

Uses

- Suitable for interior use only.
- Finishing plaster for use over natural plasters or modern substrates.

Colours and Gloss

- Soft white. Can be tinted to a wide range of colours using oxides.
- ** Due to the nature of natural materials, colours may reflect and vary under different lighting conditions. Available colours are limited to a range of natural mineral tones. Suitable for tinting to a wide range of natural colours, however, bright, highly saturated or "plastic-toned" paint colours may not be achievable.

Coverage Rate: Approximately 4m²/15kg bag @2mm build

Coverage rates vary according to substrate, application technique, wastage factors and substrate preparation.

Application Method: Trowel

Dry Film Build: 2 – 6mm

Typical Data at 25°C and 50% Relative Humidity

Drying Time: 24 to 48 hours

Curing Time: 7 days

No of Coats: 2

Clean Up: Water

Packaging Sizes: 15kg

Substrate Conditions

- Substrate must be installed as per manufacturer's specifications.
- Substrate must be clean and free of dust, dirt, oil, salt, mould or any other contamination.
- Any base coats should be fully cured.
- Substrates must not contain more than 15% moisture prior to the application of Rockcote Clay Plaster Decor.

Mixing

Add one 15kg bag of Rockcote Clay Plaster Décor to 3 - 3.5 litres of clean water. Mix for a minimum of 3 minutes. Allow mixture to sit for 10 - 15 minutes and adjust consistency, if required, before use.

Application

- Rockcote Clay Plaster Décor can be applied by a traditional hawk and trowel, screeded, floated, trowelled, sponged, texture brushed and undulated to give many desired texture finishes.
- Clean and dry chopped wheat straw, hemp hurd, rice husks, quartz chips, marble chips, chopped wheat or rice straw can be added.

Rockcote Clay Plaster Decor (Dry)

Active From:

23 Jul 2026

Precautions and Limitations

- Rockcote Clay Plaster Décor should not be applied in temperatures below 5°C or above 35°C.
- Rockcote Clay Plaster Décor is not suitable for areas of continual damp or areas submerged in water.
- Not suitable for external application or wet areas such as shower recesses or splashbacks.
- Rockcote does not recommend the use of any Rockcote Natural Materials on floors.

Transport and Storage

Rockcote Clay Plaster Decor must be kept dry during transport and storage.

Disposal

- Dispose of in accordance with local council regulations

Safety Data

Refer to: Rockcote Clay Plaster Décor (Dry) Safety Data Sheet

Item Number

3443

Disclaimer

Rockcote Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, Rockcote Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.