

Rockcote EcoStyle Sealer/Undercoat

Active From:

16 Sep 2025

Rockcote EcoStyle Sealer/Undercoat is a premium quality very low VOC [Volatile Organic Compound] water-borne paint manufactured using high quality resins and binders. Areas painted with Rockcote EcoStyle Sealer/Undercoat have no lingering paint fumes. Rockcote EcoStyle Sealer/Undercoat dries to a hard sandable finish that provides excellent adhesion for subsequent top coats.

Features

- Water based.
- Very low roller spatter.
- High level of adhesion.
- Low VOC 0.4gm/L.

Uses

- Rockcote EcoStyle Sealer/Undercoat is suitable for interior application over properly prepared substrates such as fibre cement sheeting, previously painted surfaces and plasterboard.
- Ideal for use prior to the application of Rockcote Natural Materials, Coloured Renders, texture coatings or base coats.

Colours and Gloss

- White base but can be tinted to soft colours.
- NB: Should be tinted when over coating strong vibrant colours.

Sheen Level: Flat

Coverage Rate: 16m²/ltr

Coverage rates vary according to substrate, application technique, wastage factors and substrate preparation.

Application Method: Brush, Roller or Spray

Dry Film Build: 27 microns

Wet Film Build: 71 microns

Typical Data at 25°C and 50% Relative Humidity

Drying Time: 2 hours

Touch Dry: 30 minutes

Dry to Recoat: 2 hours

No of Coats: 1

Clean Up: Water

Packaging Sizes: 15L

Thinning: Up to 5% water

Substrate Conditions

- All substrates must be properly prepared and be free of dirt, dust, grime and any other contaminants.
- Substrates must not contain more than 15% wood moisture equivalent (WME).
- Do not apply if air and surface temperatures are below 10°C or above 35°C.

Application

- If using multiple pails, contents must be boxed together to ensure colour consistency.
- Be sure to keep a wet edge with this product and plan your work to suit the product and weather conditions. See the Rockcote technical article on cutting in and avoiding "picture framing".
- For airless spray use 0.013 - 0.017 inch spray tips and adjust the flow rate and fan width to minimise water required to thin.
- Only thin down the amount needed for the project and use within three days.
- Do not pour thinned material back into un-thinned material.

Rockcote EcoStyle Sealer/Undercoat

Active From:

16 Sep 2025

Precautions and Limitations

- Rockcote EcoStyle Sealer/Undercoat should not be applied in temperatures below 10°C or above 35°C.
- Rockcote EcoStyle Sealer/Undercoat is not suitable for areas of continual damp or areas submerged in water.

Transport and Storage

- Store in a cool, dark place.
- Keep pail sealed.
- Do not stack over 3 high.

Disposal

- Spilt Material must be absorbed with sand/sawdust and lifted for proper disposal
- Product must not be allowed to run into drains or open bodies of water
- Residual small amounts of leftover paint on brushes and rollers should be wiped on to an old newspaper and allowed to dry, rather than being washed down the sink. Dispose of in accordance with local council regulations
- Suitable for disposal through the RA Industries Reclaimer Portable Paint Wash Recycling System

Safety Data

Refer Rockcote EcoStyle SDS

Disclaimer

Rockcote Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, Rockcote Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.