

Rockcote Otsumigaki

Active From:

30 Jun 2026

Rockcote Otsumigaki is a premium premixed clay and lime plaster for internal applications. Inspired by traditional Japanese finishing techniques, it produces a smooth, polished finish with subtle depth and natural variation. The breathable mineral surface can be worked from a soft sheen through to a high lustre, creating a refined handcrafted appearance.

Features

- Premium Clay & Lime Formulation - natural mineral composition.
- Polishable Finish - from a soft sheen through to a high-lustre finish.
- Breathable - supports moisture vapour movement.

Uses

- **Suitable for internal use only.**
- Finishing plaster for use over natural plasters or modern substrates.

Colours and Gloss

- Natural to off-white colour.
- Can be tinted to a wide range of colours using paint tints or alkaline resistant oxides.

Sheen Level: Can be polished to lustre or glass finish

Coverage Rate: 20m²/15ltr @ 1mm thickness

Coverage rates vary according to substrate, application technique, wastage factors and substrate preparation.

Application Method: Stainless Steel Trowel/Japanese Trowel

Dry Film Build: 0.5mm-1.5mm

Typical Data at 25°C and 50% Relative Humidity

Drying Time: 24 to 48 hours

Touch Dry: 30-60 minutes

Dry to Recoat: 30-60 minutes

No of Coats: 2

Clean Up: Water

Packaging Sizes: 15L, 4L

Water Resistance: None

Substrate Conditions

- Substrate must be installed as per manufacturer's specifications.
- Substrate must be clean and free of dust, dirt, oil, salt, mould or any other contamination.
- Any base coats should be fully cured prior to application of Rockcote Otsumigaki.
- Substrates must not contain more than 15% moisture prior to the application.
- For full details on application for each substrate, refer to the Rockcote Natural Materials Systems Guide.

Mixing

- Rockcote Otsumigaki is pre-mixed but should be properly stirred prior to application.



Rockcote Otsumigaki

Active From:

30 Jun 2026

Application

- Apply with hawk and trowel; finish with Japanese trowel.
- Apply in 2 thin coats (wet on wet); allow to dry for 12 hours.
- For best results on flat substrates, apply 2 coats to 0.5mm film build.
- To polish, apply fine mist of Liquid Carnauba Wax and polish with Japanese trowel.
- The application of Rockcote Natural Materials is a highly skilled process that requires experience working with natural building products and systems. It is the responsibility of the applicator to select the right materials for the job and ensure correct installation and application according to the guidelines in the Rockcote Natural Materials Systems Guide and the attached specification. Rockcote strongly recommends that all Rockcote Natural Materials be applied by a licensed tradesperson who has extensive experience in applying the product for a similar application to the project at hand. Rockcote is not responsible for the ongoing maintenance of the Natural Material finishes, which is required in the upkeep and performance of the coating.

Precautions and Limitations

- Rockcote Otsumigaki is highly alkaline due to the inclusion of hydrated lime. Please ensure adequate PPE is used when mixing and applying.
- Care must be taken not to exceed the maximum film build recommendations or cracking of the dried film may occur.
- Many substrates can be coated with Rockcote Otsumigaki, but the high alkalinity may affect the underlying coating. Always contact Rockcote or refer to the Rockcote Natural Materials Systems Guide before using.
- Should not be applied in temperatures below 5°C or above 35°C.
- Not suitable for areas of continual damp or areas submerged in water.
- Not suitable for external application or wet areas such as shower recesses or splashbacks.
- Rockcote does not recommend the use of any Rockcote Natural Materials on floors.

Transport and Storage

- Store in a cool, dark place.
- Keep pail sealed.
- Do not stack 15 litre pails over 3 pails high.

Disposal

- Dispose of in accordance with local council regulations

Safety Data

Refer Rockcote Otsumigaki SDS.

Item Number

5151, 5152

Disclaimer

Rockcote Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, Rockcote Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.