

Technical Data Sheet

ROCKCOTE PVC PANEL PRIMER

Effective From 14 Jan, 2021

ROCKCOTE PVC Panel Primer is a high performance primer specially designed for outstanding adhesion to PVC substrates without sanding. ROCKCOTE PVC Panel Primer is ideal as a primer for use with ROCKCOTE high performance membranes and paint. ROCKCOTE PVC Panel Primer with grit is the ideal primer for use with ROCKCOTE coloured textures.

Features

- Water based
- Highly adhesive over PVC panels
- Light grey
- Interior or Exterior

Benefits

- Quick drying
- No sanding required

Uses

- Gives excellent adhesion over PVC panels and can be overcoated with ROCKCOTE membranes, paints and textures.

Colours and Gloss

- Light grey.
- Do not tint.

Sheen Level

Coverage Rate

6 - 10m²/ltr

Approximately 10 square metres per litre, 6-8 square metres per litre with grit added. Figures are a guide only. Coverage rates vary according to substrate texture, application technique, wastage factors and substrate preparation.

Application Method

Brush or Long Nap Roller

Dry Film Build

Wet Film Build

Typical Data at 25°C and 50% Relative Humidity

Drying Time 2 hours
Touch Dry 30 mins
Dry to Recoat 2-4 hours

Usual No Coats 1

Clean Up Water

Packaging Sizes Trade 20L 15L 10L 4L 1L

Volume Solids

Thinning Do not thin

Elongation Rate

Crack Bridging

Abrasion Resistance

Moisture Control

Water Resistance

Technical Data Sheet

ROCKCOTE PVC PANEL PRIMER

Effective From	14 Jan, 2021
-----------------------	--------------

Substrate Conditions

- Surfaces should be clean, dry and free from loose or crumbling material, oil or form release agents.
- All substrates must be installed as per manufacturers' specifications prior to application.
- Not suitable for areas that will be submerged in water or subjected to continual moisture.

Application

- The application of this product is a specialist procedure which should be carried out by a skilled and experienced applicator.
- Must be applied evenly and consistently to provide colour consistency and opacity for top coats.
- Can be applied with a quality brush or 15-20mm long nap sheepskin roller.

Precautions and Limitations

- Should not be applied in air and surface temperatures below 5°C or above 35°C.
- ROCKCOTE Primers should only be used over sound clean substrates, and are not suitable for areas that will be submerged in water or subjected to continual moisture.
- ROCKCOTE PVC Panel Primer must only be used on substrates with a moisture level of less than 15% WME.
- ROCKCOTE Primers are not suitable for use direct to substrate below damp proof installments.

Transport and Storage

- Store in a cool dark place.
- Keep pail sealed.
- Do not stack over 3 high.

Disposal

- Spilt Material must be absorbed with sand/sawdust and lifted for proper disposal
- Product must not be allowed to run into drains or open bodies of water
- Residual small amounts of leftover paint on brushes and rollers should be wiped on to an old newspaper and allowed to dry, rather than being washed down the sink. Dispose of in accordance with local council regulations
- Suitable for disposal through the RA Industries Reclaimer Portable Paint Wash Recycling System

Safety Data

Refer to ROCKCOTE PVC Panel Primer

Disclaimer

ROCKCOTE Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, ROCKCOTE Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.