

Rockcote Quick Render Non-combustible

Active From:

22 May 2026

Rockcote Quick Render Non-combustible is a high performance, pre blended polymer modified cement render specifically designed to meet Australian Standards in combustibility for building materials and is fully compliant with AS1530.1. Rockcote Quick Render Non-combustible is water resistant, reducing the risk of efflorescence or rising damp and provides an excellent base coat for subsequent full Rockcote texture coating systems. Rockcote Quick Render Non-combustible has excellent strength and adhesion and is suitable for both residential and commercial applications requiring fire compliance and long term durability.



Features

- Easy to apply
- Pre blended
- AS1530.1 compliant
- Superior strength
- Excellent adhesion

Uses

- Suitable for interior and exterior use
- For application over properly prepared substrates including For application over properly prepared substrates including brick, block, Tilt up/Off form concrete, AAC panels/blocks, Core Filled Fibre Cement and Core Filled PVC
- Rockcote Quick Render Non-combustible is ideal to use as a base coat for Rockcote Coloured Renders, acrylic textures, membrane paints, and roll on finishes.
- Rockcote Quick Render Non Combustible Render must be overcoated within 28 days of application.

Coverage Rate: 2m²/20kg @ 5mm build

Application Method: Trowel or Spray

Dry Film Build: 4-10mm

Wet Film Build: 4-10mm

Typical Data at 25°C and 50% Relative Humidity

Drying Time: 8 hours

Curing Time: 48-72 hours

Drying times will vary with changes in air and substrate temperature, humidity and residual moisture in the substrate.

No of Coats: 1-2

Clean Up: Clean with water immediately after use if render has not cured. Remove any unwanted material or spatter from surfaces with water as soon as possible and preferably before dry. Recently dried render may be more easily removed with warm water and detergent.

Packaging Sizes: 20kg

Rockcote Quick Render Non-combustible

Active From:

22 May 2026

Substrate Conditions

- Contact Rockcote for a custom specification to suit your combustibility requirements.
- Ensure substrates are properly prepared and free of dirt, dust, grime, oil, salt, mould, release agents and any other contaminants.
- Do not apply Rockcote Quick Render Non-combustible if air and surface temperatures are below 5°C or above 35°C.
- Brick and masonry substrates must be wet down prior to the application of Rockcote Quick Render Non-combustible. Application should proceed when the wet "shine" has disappeared.
- When using AAC panels or blocks, apply Rockcote Rockbond 27 prior to the application of Quick Render to control absorption, improve adhesion, minimise joint grinning and allow a greater working time.
- For dense, smooth and difficult substrates, Rockcote recommends the use of Rockcote High Adhesion Primer prior to the application of Rockcote Quick Render Non-Combustible.

Mixing

Mix 20kg of Rockcote Quick Render Non-combustible to 3-3.5L of cool, clean water and stir for a minimum of 2 minutes. Let stand for 2-3 minutes before remixing and adjusting to the desired consistency.

Application

- A water bead test must be carried out prior to application, to ensure no bond breakers or release agents are present (on the surface)
- The two-step application "wet on wet" method helps firmly press the render onto the surface, improving adhesion. Apply a tight first coat of Rockcote Quick Render Non-combustible, allow it to take up on the wall, then follow with an additional skim coat and finish as required.
- Once initial dry set has occurred, rewet 2 to 3 times a day with clean water for 2 days. This is especially important during hot and/or windy weather conditions.
- Rockcote Quick Render Non-combustible can be sprayed on with a suitable machine.
- Rockcote Quick Render Non-combustible can be floated and sponged or just shaved if applying a Rockcote Coloured Render system.
- Rockcote Quick Render Non Combustible Render must be overcoated within 28 days of application.
- All windows and doors should be masked up to avoid damage and for ease of cleaning.
- Keep the finished Rockcote Quick Render Non-combustible sheltered from rain and moisture for 24 hours after completion dependent on climatic conditions.

Precautions and Limitations

- Rockcote Quick Render Non-combustible is not suitable for application in swimming pools.
- When working with Rockcote Quick Render Non-combustible, observe the usual precautions for handling cement based products.
- Avoid inhalation of the powder, prolonged skin contact and particularly eye contact.
- If contact occurs, flush thoroughly with clean water.
- Wear protective clothing to minimise skin contact and wear goggles where spatter is likely.

Transport and Storage

- Rockcote Quick Render Non-combustible must be kept dry during transportation and storage.
- Where spills occur, sweep up dry material or soak up liquid spillage with sand/sawdust and remove to suitable disposal.
- Store in a cool dark place
- Keep pail sealed
- Do not stack over 3 high

Disposal

- Dispose of in accordance with local council regulations

Safety Data

Refer Rockcote Quick Render Non-combustible SDS.

Rockcote Quick Render Non-combustible

Active From:

22 May 2026

Disclaimer

Rockcote Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, Rockcote Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.