

# Technical Data Sheet

## ROCKCOTE TUSCANY TROWEL ON

**Effective From** 26 Jul, 2023

ROCKCOTE Tuscany Trowel On is specifically formulated to be a highly crack resistant, flexible acrylic texture render. Available in a medium and a coarse finish, ROCKCOTE Tuscany Trowel On provides economy without compromising on quality.

### Features

- Water based
- Excellent adhesion qualities
- Economical

### Benefits

- Easy to apply and finish
- Flexible
- Highly crack resistant

### Uses

- Suitable for application over properly primed and prepared substrates such as brick, block, cement render, off-form concrete, previously painted masonry, ROCKCOTE render, concrete, fibre cement sheeting, A.A.C. panels/blocks and plasterboard.
- Can be used interior and exterior.
- Must be overcoated with ROCKCOTE Armour or Armour Flex.

### Colours and Gloss

Not designed as a coloured finish, but can be tinted to assist in coverage of subsequent coloured coatings. Available in light and strong bases.

**Sheen Level** Matt

**Coverage Rate** 10m<sup>2</sup>/15ltr  
Figures are a guide only. Coverage rates vary according to substrate, application technique, wastage factors and substrate preparation.

**Application Method** Trowel, then float to finish

**Dry Film Build** 1mm

**Wet Film Build**

### Typical Data at 25°C and 50% Relative Humidity

**Drying Time** 24 Hours

**Touch Dry** 3 Hours

**Dry to Recoat** 24 Hours

**Usual No Coats** 1 or 2

**Clean Up** Water

**Packaging Sizes** Trade 20L  15L  10L  4L  1L

**Volume Solids**

**Thinning**

**Elongation Rate**

**Crack Bridging** Excellent

**Abrasion Resistance** Excellent

**Moisture Control**

**Water Resistance**

**Pot Life**

# Technical Data Sheet

## ROCKCOTE TUSCANY TROWEL ON

<b>Effective From</b>	26 Jul, 2023
-----------------------	--------------

### Substrate Conditions

- Must be applied over properly prepared substrates that are free of dirt, dust, grime and any other contaminants.
- Substrates must not contain more than 15% moisture (WME) prior to application.
- Do not apply if air and surface temperatures are below 10°C or above 35°C.
- If applying over ROCKCOTE Quick Render, application may proceed after 48hrs if properly cured.
- Fresh cementitious substrates such as site mix sand & cement render and concrete must be left for up to 28 days to sufficiently cure, prior to application.

### Application

- The ROCKCOTE Tuscan Trowel On is normally trowelled on to the surface in one or two applications and finished with a plastic float.
- Allow proper ventilation for good air flow to aid in the drying process.
- Rockcote Tuscan Trowel On must be overcoated within 14 days.
- Ideal humidity level for application is between 50% & 60%.

### Precautions and Limitations

- Should not be applied in temperatures below 10°C or above 35°C.
- Not suitable for areas of continual damp or areas submerged in water.
- Must be overcoated with a ROCKCOTE protective membrane.

### Transport and Storage

- Store in a cool dark place
- Keep pail sealed
- Do not stack over 3 high

### Disposal

- Dispose of in accordance with local council regulations

### Safety Data

Refer ROCKCOTE Tuscan Trowel On SDS.

### Disclaimer

Rockcote Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, Rockcote Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.