

Technical Data Sheet

ROCKCOTE TUSCANY TROWEL ON

Effective From 13 May, 2021

ROCKCOTE Tuscany Trowel On is specifically formulated to be a highly crack resistant, flexible acrylic texture render. Available in a medium and a coarse finish, ROCKCOTE Tuscany Trowel On provides economy without compromising on quality. While this product can be tinted to assist with colour vibrancy, it should be overcoated with ROCKCOTE Armour.

Features

- Water based
- Excellent adhesion qualities
- Economical
- Available in summer and winter grade bases for better workability.

Benefits

- Easy to apply and finish
- Flexible
- Highly crack resistant

Uses

- Suitable for application over properly primed and prepared substrates such as brick, block, cement render, off-form concrete, previously painted masonry, ROCKCOTE render, concrete, fibre cement sheeting, A.A.C. panels/blocks and plasterboard.
- Can be used interior and exterior.
- Must be overcoated with ROCKCOTE Armour.

Colours and Gloss

Not designed as a coloured finish, but can be tinted to assist in coverage of subsequent coloured coatings.
Available in light and strong bases.

Sheen Level Matt

Coverage Rate 12m²/15ltr
Figures are a guide only. Coverage rates vary according to substrate, application technique, wastage factors and substrate preparation.

Application Method Trowel, then float to finish

Dry Film Build 1mm

Wet Film Build

Typical Data at 25°C and 50% Relative Humidity

Drying Time 24 Hours

Touch Dry 3 Hours

Dry to Recoat 24 Hours

Usual No Coats 1 or 2

Clean Up Water

Packaging Sizes Trade 20L ☐ 15L ☒ 10L ☐ 4L ☐ 1L ☐

Technical Data Sheet

ROCKCOTE TUSCANY TROWEL ON

Effective From	13 May, 2021
-----------------------	--------------

Volume Solids

Thinning

Elongation Rate

Crack Bridging Excellent

Abrasion Resistance Excellent

Moisture Control

Water Resistance

Substrate Conditions

- Must be applied over properly prepared substrates that are free of dirt, dust, grime and any other contaminants.
- Substrates must not contain more than 15% moisture (WME) prior to application.
- Do not apply if air and surface temperatures are below 10°C or above 35°C.
- If applying over ROCKCOTE Quick Render, application may proceed after 48hrs if properly cured.
- Fresh cementitious substrates such as site mix sand & cement render and concrete must be left for up to 28 days to sufficiently cure, prior to application.

Application

- The ROCKCOTE Tuscany Trowel On is normally trowelled on to the surface in one or two applications and finished with a plastic float.
- The most ideal air temperature for application of Winter Grade formulations is 15°C to 20°C, depending upon the weather conditions.
- The most ideal air temperature for application of Summer Grade formulations is above 20°C, depending upon the weather conditions.
- Allow proper ventilation for good air flow to aid in the drying process.
- Ideal humidity level for application is between 50% & 60%.

Precautions and Limitations

- Should not be applied in temperatures below 10°C or above 35°C.
- Not suitable for areas of continual damp or areas submerged in water.
- Must be overcoated with a ROCKCOTE protective membrane.

Transport and Storage

- Store in a cool dark place
- Keep pail sealed
- Do not stack over 3 high

Disposal

- Dispose of in accordance with local council regulations

Technical Data Sheet

ROCKCOTE TUSCANY TROWEL ON

Effective From	13 May, 2021
-----------------------	--------------

Safety Data

Refer ROCKCOTE Tuscany Trowel On SDS.

Disclaimer

ROCKCOTE Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, ROCKCOTE Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.