Technical Data Sheet



ROCKCOTE VELVETINA

Effective From 21 Sep, 2020

ROCKCOTE Velvetina is a traditional lime plaster developed to be the ideal base coat for ROCKCOTE Venetian Plaster. ROCKCOTE Velvetina is beautiful in its own right, perfect and ideal for providing a natural concrete finish with the ability to be tinted to a wide range of colours. This speciality finish is beautiful with a natural patina.

Features

- Can be used as a base coat for ROCKCOTE Venetian Plaster.
- Can also be used as a finish coat to create a smooth to lustre finish.
- A variety of patterns can be created depending on the skill of the applicator.
- · Zero VOC.

Benefits

- Intended as a base coat layer to address substrate imperfections, particularly over plasterboard or fibre cement sheet, in preparation for over coating with Venetian Plaster.
- Premixed product, just stir and apply.

Uses

- As a top coat ROCKCOTE Velvetina is suitable for interior use excluding wet areas.
- Ideal for use as a base coat for ROCKCOTE Venetian Plaster.

Colours and Gloss

- Natural to off white colour.
- Can be tinted to various colours using paint tints or alkaline resistant oxides.
- ROCKCOTE recommends not exceeding 4% of product weight in oxide addition.

Sheen Level Flat to Lustre

Coverage Rate 30m2/15ltr

Application Method Venetian Stainless Steel Trowel

Dry Film Build 0.5 to 1mm

Wet Film Build

Typical Data at 25°C and 50% Relative Humidity

Drying Time 12 hours

Touch Dry

Dry to Recoat 12 hours

Usual No Coats 1st as a base coat; 2nd as a finishing coat system

Clean Up Water

Packaging Sizes Trade 20L 15L 10L 4L 1L

Volume Solids 50

Thinning Not normally required.

Elongation Rate Crack Bridging Abrasion Resistance Moisture Control Water Resistance

Technical Data Sheet



ROCKCOTE VELVETINA

Effective From 21 Sep, 2020

Substrate Conditions

- Substrate must be installed as per manufacturer's specifications.
- Substrate must be clean and free of dust, dirt, oil, salt, mould or any other contamination.
- Any base coats should be fully cured. Substrates must not contain more than 15% moisture prior to the application of the ROCKCOTE system.
- For full details on application for each substrate, refer to the ROCKCOTE Natural Materials Systems Guide.

Mixing Product in pail will consist of a lime putty with a protective water layer on top.

Simply mix until consistent before applying.

Apply in a thin layer over surface and work with a steel trowel.

Precautions and Limitations

- ROCKCOTE Velvetina is highly alkaline due to the inclusion of hydrated lime. Please ensure adequate PPE is used when mixing and applying.
- Many substrates can be coated with ROCKCOTE Velvetina but the high alkalinity may affect the
 underlying coating. Always contact ROCKCOTE or refer to the ROCKCOTE Natural Materials Systems
 Guide before using.
- ROCKCOTE Velvetina should not be applied in temperatures below 5°C or above 35°.
- ROCKCOTE Velvetina is not suitable for wet areas.
- ROCKCOTE recommends that this product be applied by a licensed tradesperson who has extensive
 experience in applying these products for similar applications to your particular project. The
 success of each project requires the tradesperson to have a thorough technical knowledge of
 appropriate building design, substrate conditions and their client expectations to determine if
 ROCKCOTE Velvetina is fit for the purpose expected for your particular project.

Transport and Storage

- Store in a cool, dark place.
- Do not stack more than 3 high.
- Keep pail sealed.

Disposal

• Dispose of in accordance with local council regulations

Safety Data

Refer to ROCKCOTE Velvetina SDS..

Disclaimer

ROCKCOTE Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, ROCKCOTE Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.