

## Rockcote MicroFinish III Penetrating Sealer

Active From:

21 Jun 2024

Rockcote MicroFinish III Penetrating Sealer is a clear and penetrative coating that increases the durability of Rockcote MicroStone product. As part of the Rockcote MicroStone Range, MicroFinish III Penetrating Sealer is ideal for use as a preparation for sealing and extra protection.

### Features

- Water based
- Ease of use
- Vapour permeable

### Uses

- Enhances hardness and durability of the surface when applied over Rockcote MicroStone.
- Suitable for Interior and Exterior use.

### Colours and Gloss

Clear, then dries clear

<b>Sheen Level:</b>	Flat
<b>Coverage Rate:</b>	18 to 20m <sup>2</sup> /ltr
<b>Application Method:</b>	Sponge

### Typical Data at 25°C and 50% Relative Humidity

<b>Drying Time:</b>	4 hours
<b>Touch Dry:</b>	30 minutes
<b>Dry to Coat:</b>	1 hour

<b>No of Coats:</b>	2
<b>Clean Up:</b>	Water
<b>Packaging Sizes:</b>	4L

### Substrate Conditions

- Must be applied over properly prepared substrates that are free of dirt, dust, grime and any other contaminants.
- All substrates must be installed as per manufacturers specifications prior to application.
- Do not apply if air and surface temperatures are below 5°C or above 35°C.
- The moisture content in the substrate must be below 15% WME (Wood Moisture Equivalent) prior to and during the application of the specified Rockcote MicroStone coating system.

### Mixing

- Product to be thinned down; 2 parts MicroFinish III Penetrating sealer to 1 part water
- Stir well before use.

### Application

- Apply Rockcote MicroFinish III Penetrating Sealer with a sponge in an even, uniform and consistent manner, avoiding runs or flooding the surface.
- Care should be taken not to apply too much product on cut-in areas.

## Rockcote MicroFinish III Penetrating Sealer

Active From:

21 Jun 2024

### Precautions and Limits

- Rockcote MicroFinish III Penetrating Sealer will last up to 5 years depending on the exposure.
- Yearly maintenance inspection should be carried out as per the Rockcote Maintenance Guide.
- Rockcote MicroFinish III Penetrating Sealer will not bridge or seal cracks.
- Insufficient coverage of Rockcote MicroFinish III Penetrating Sealer will diminish the effectiveness of the coating.
- Should not be applied over glossy silicone based paints or sealants.
- Not recommended for floors.
- Not suitable for areas totally immersed in water or swimming pools.
- MicroFinish III Penetrating Sealer is not designed for application under MicroFinish I Epoxy Sealer.

### Transport and Storage

- Store in a cool dark place
- Keep pail sealed
- Do not stack over 2 high

### Disposal

- Spilt Material must be absorbed with sand/sawdust and lifted for proper disposal
- Product must not be allowed to run into drains or open bodies of water
- Residual small amounts of leftover paint on brushes and rollers should be wiped on to an old newspaper and allowed to dry, rather than being washed down the sink. Dispose of in accordance with local council regulations
- Suitable for disposal through the RA Industries Reclaimer Portable Paint Wash Recycling System

### Safety Data

Refer to Rockcote MicroFinish III Penetrating Sealer SDS.

### Disclaimer

Rockcote Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, Rockcote Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.