

Rockcote MicroPrime

Active From:

21 Jun 2024

Rockcote MicroPrime is an acrylic bonding agent designed to be used as a primer and to control suction over highly absorbent and difficult substrates. Rockcote MicroPrime is supplied ready for use and does not require thinning.

Features

- Easy to use
- Excellent adhesion qualities
- Fast dry to recoat time
- Controls drying time of subsequent coating.

Benefits

- Reduces suction and improves adhesion
- Allows for easier application
- increasing working time

Uses

- Suitable for Interior and Exterior use.
- Can be applied to both vertical and horizontal surfaces.
- Can also be used as a primer for high suction substrates.

Coverage Rate:	12-15m ² /ltr
Application Method:	Roller, brush or spray
Dry Film Build:	7-10 microns
Wet Film Build:	40 microns

Typical Data at 25°C and 50% Relative Humidity

Drying Time:	4 hours
Touch Dry:	30 minutes
Dry to Coat:	2 hours

No of Coats:	1-2
Clean Up:	Water
Packaging Sizes:	4L

Substrate Conditions

- Must be applied over properly prepared substrates that are free of dirt, dust and any other contaminants.
- All substrates must be installed as per manufacturers specifications prior to application.
- The moisture content in the substrate must be below 15% WME (Wood Moisture Equivalent) prior to and during the application of the specified Rockcote MicroStone coating system.

Application

- Must be mixed before use to ensure consistency of the product.
- Rockcote MicroBase must be allowed to dry for a minimum 48 hours before applying Rockcote MicroPrime.
- Apply using a 10mm nap synthetic roller.
- Care should be taken not to apply excessive product when cutting in areas or during application.

Precautions and Limits

- Only to be used for the specified purposes.
- Not suitable for areas totally immersed in water or swimming pools.
- Avoid puddling, pooling or excessive film build greater than 20 microns of the MicroPrime.

Transport and Storage

- Store in a cool dark place
- Keep pail sealed
- Do not stack over 2 high

Rockcote MicroPrime

Active From:

21 Jun 2024

Disposal

- Spilt Material must be absorbed with sand/sawdust and lifted for proper disposal
- Product must not be allowed to run into drains or open bodies of water
- Residual small amounts of leftover paint on brushes and rollers should be wiped on to an old newspaper and allowed to dry, rather than being washed down the sink. Dispose of in accordance with local council regulations
- Suitable for disposal through the RA Industries Reclaimer Portable Paint Wash Recycling System

Safety Data

Refer Rockcote MicroPrime SDS.

Disclaimer

Rockcote Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, Rockcote Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.