



Mortatec Pty Ltd

Classic Render

Technical Data Sheet

Mortatec Classic Bond is an acrylic bonding agent designed to be added to the Mortatec Classic Render range to increase adhesion and strength. Mortatec Classic Bond is also suitable to be used as a primer to reduce suction over highly absorbent substrates, such as AAC.

FEATURES	BENEFITS	USES
<ul style="list-style-type: none">• Easy to use• Excellent adhesion qualities	<ul style="list-style-type: none">• Will provide a stronger and harder render, when used as an additive to Mortatec Classic Render (please refer to Mortatec Classic Render TDS).• Mortatec Classic Render is suitable as a primer to reduce suction over highly absorbent substrates such as AAC.	<ul style="list-style-type: none">• Adding to cement based render• Priming high suction substrates

Colours and Gloss

Sheen Level

Coverage Rate 12-15m²/ltr

Application Method Roller, brush or spray

Dry Film Build 7-10 microns

Wet Film Build 40 microns

Typical Data at 25oC and 50% Relative Humidity

Drying Time 4 hours

Touch Dry 30 minutes

Dry to Recoat 2 hours

Usual No Coats

Clean Up Water

Packaging Sizes Trade 20L & 5L

Volume Solids 27

Thinning

Elongation Rate

Crack Bridging

Abrasion Resistance

Moisture Control

Water Resistance

Pot Life

Substrate Conditions

- Must be applied over properly prepared substrates that are free of dirt, dust and any other contaminants.
- All substrates must be installed as per manufacturers' specifications prior to application.

Application

- When adding to Mortatec Classic Render, add 20% Mortatec Classic Bond to water and use as gauging liquid.
- Can be used as a primer over AAC.

Precautions and Limitations

- Only to be used for specified purposes.

Transport and Storage

- Store in a cool dark place
- Keep pail sealed
- Do not stack over 2 high

Disposal

- Spilt Material must be absorbed with sand/sawdust and lifted for proper disposal
- Product must not be allowed to run into drains or open bodies of water
- Residual small amounts of leftover paint on brushes and rollers should be wiped on to an old newspaper and allowed to dry, rather than being washed down the sink. Dispose of in accordance with local council regulations
- Suitable for disposal through the RA Industries Reclaimer Portable Paint Wash Recycling System

Safety Data

Refer Mortatec Classic Bond SDS.

Disclaimer

Mortatec Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, Rockcote Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.