

MICROSTONE Slip Rating Results



Durable Beauty.

MicroStone is easy to use and offers excellent adhesion qualities. Durable and easy to maintain when sealed, it provides a unique appearance that embodies the true essence of luxury. Suitable for properly primed and prepared substrates such as brick, block, cement render, Rockcote render, concrete, cement sheeting, and plasterboard. MicroStone can also be over-coated with Rockcote MicroFinish Sealers for added durability and lower maintenance on walls, floors, and wet area applications.

Application System

System	Wet Pendulum Slip Rating	Dry Pendulum Slip Rating
Vertical Surfaces - 2 x coats of MicroFinish IV		
MicroPrime - 1st coat		
MicroStone - 1st coat		
MicroStone - 2nd coat		
Lightly sanded with sandpaper - PS11A P240	P2	D1
MicroFinish III Penetrating Sealer - 1 coat		
MicroFinish IV Hydrophobic Sealer (MS 20) - 1st coat		
MicroFinish IV Hydrophobic Sealer (MS 20) - 2nd coat (after 1 hour)		
Wet Area Horizontal Surfaces - 2 x coats of MicroFinish IV (with anti slip additive)		
MicroPrime - 1st coat		
MicroStone - 1st coat		
MicroStone - 2nd coat		
Lightly sanded with sandpaper - PS11A P240		
MicroFinish III Penetrating Sealer - 1 coat		
MicroFinish IV Hydrophobic Sealer (MS 20) +2.4% ptex 50 - 1st coat		
MicroFinish IV Hydrophobic Sealer (MS 20) +2.4% ptex 50 (Anti Slip additive) - 2nd coat (after 1 hour)	P4	D1
Vertical Surfaces - 2 x coats of MicroFinish II		
MicroPrime - 1st coat		
MicroStone - 1st coat		
MicroStone - 2nd coat		
Lightly sanded with sandpaper - PS11A P240		
MicroFinish III Penetrating Sealer - 1 coat		
MicroFinish II Polyurathane - 1st coat		
MicroFinish II Polyurathane - 2nd coat (after 3 hours)	P2	D1
Wet Area Horizontal Surfaces - 2 x coats of Microfinish II (with anti slip additive)		
MicroPrime - 1st coat		
MicroStone - 1st coat		
MicroStone - 2nd coat		
Lightly sanded with sandpaper - PS11A P240		
MicroFinish III Penetrating Sealer - 1 coat		
MicroFinish II Polyurathane - 1st coat		
MicroFinish II Polyurathane +2.4% ptex 50 (Anti Slip Additive) - 2nd coat (after 3 hours)	P5	D1



Phone: 1300 736 668 Head Office: 18 Machinery Road, Yandina QLD 4561 Email: sales@rockcote.com.au Web: www.rockcote.com.au