

Rockcote Clay Paint Casa

Active From:

30 Jun 2026

Rockcote Clay Paint Casa is a clay-based natural paint designed to create a smooth, ultra-matte mineral finish with a soft, uniform appearance. Formulated from fine clays and mineral fillers, it provides a breathable coating.



Features

- Natural Mineral Finish - Smooth, ultra-matte appearance.
- Breathable - Allows moisture vapour to pass through helping walls breathe.
- Low VOC & Low Odour - Based on natural mineral ingredients.

Uses

- **Suitable for internal use only.**
- Ideal for application over properly prepared substrates including brick, block, concrete, cement render, Rockcote render, fibre cement sheet, AAC panels/blocks and plasterboard.

Colours and Gloss

- Tint Guide: Deep Base-P (Paint formula)
- Can be tinted to wide range of colours.

****** Due to the nature of natural materials, colours may reflect and vary under different lighting conditions. Available colours are limited to a range of natural mineral tones. Suitable for tinting to a wide range of natural colours, however, bright, highly saturated or “plastic-toned” paint colours may not be achievable.

Sheen Level: Soft matt finish.

Coverage Rate: 8-12m² per Litre

Coverage rates vary according to substrate, application technique, wastage factors and substrate preparation.

Application Method: Bush or Roller

Dry Film Build: Approximately 45 microns per coat.

Typical Data at 25°C and 50% Relative Humidity

Drying Time: 24-48 hours depending on substrate and ventilation.

Dry to Recoat: 1-2 hours

No of Coats: 2

Clean Up: Water

Packaging Sizes: 15L, 4L

Water Resistance: None

Substrate Conditions

- Substrate must be installed as per manufacturer's specifications.
- Substrate must be clean and free of dust, dirt, oil, salt, mould or any other contamination.
- Any base coats should be fully cured.
- Substrates must not contain more than 15% moisture prior to the application of Rockcote Clay Plaster Decor.
- For full details on application for each substrate, refer to the Rockcote Natural Materials Systems Guide.

Mixing

- Stir well before use and during application.

Rockcote Clay Paint Casa

Active From:

30 Jun 2026

Application

- Always check the colour before use and ensure the same batch numbers are used on a single wall where possible to avoid variation.
- Mix well before use and during application.
- Apply with brush or roller. For roller application use 10mm nap roller.
- If joining up previous days application, it is good working practice to start and finish on an external or internal corner.
- Rockcote Clay Paint Casa should only be applied in temperatures between 5°C and 35°C.
- The application of Rockcote Natural Materials is a highly skilled process that requires experience working with natural building products and systems. It is the responsibility of the applicator to select the right materials for the job and ensure correct installation and application according to the guidelines in the Rockcote Natural Materials Systems Guide and the attached specification. Rockcote strongly recommends that all Rockcote Natural Materials be applied by a licensed tradesperson who has extensive experience in applying the product for a similar application to the project at hand. Rockcote is not responsible for the ongoing maintenance of the Natural Material finishes, which is required in the upkeep and performance of the coating.

Precautions and Limitations

- Not suitable for areas of continual damp or areas submerged in water.
- Not for use over powdery, unbound or loose surfaces.
- For decorative use in interior low wear areas only.
- Not suitable for use in bathrooms.

Transport and Storage

- Store in a cool dark place.
- Keep pail sealed.
- Do not stack over 3 high.

Disposal

- Dispose of in accordance with local council regulations

Safety Data

Refer to: Rockcote Clay Paint Casa Safety Data Sheet

Item Number

7525, 7530

Disclaimer

Rockcote Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, Rockcote Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.