

Rockcote Terra Luxe

Active From:

30 Jun 2026

Rockcote Terra Luxe is a ready-to-use earthen plaster combining washed, graded aggregates with natural clay to create a textured mineral finish with subtle depth and variation. Its natural appearance is suited to both contemporary and traditional interiors, where an authentic clay finish is desired.

Features

- Natural clay with graded mineral aggregates for texture and depth
- Breathable - supports moisture vapour transmission
- Ready to Use - supplied premixed in pails.



Uses

- **Suitable for internal use only.**
- Can be overcoated with finer decorative finishes, including Rockcote Otsumigaki, Velvetina and Venetian Plaster.
- Can be customised with natural fibres, aggregates and mineral oxides to create bespoke finishes.

Colours and Gloss

- Off-white colour / Oxides
- Can be tinted to a range of colours using alkali resistant oxides
- Rockcote recommends not exceeding 4% of product weight in oxide addition.
- Fading may occur depending on type of pigment used

** Due to the nature of natural materials, colours may reflect and vary under different lighting conditions. Available colours are limited to a range of natural mineral tones. Suitable for tinting to a wide range of natural colours, however, bright, highly saturated or "plastic-toned" paint colours may not be achievable.

Sheen Level:

Matte mineral finish.

Coverage Rate:

Approximately 2-5m² per 15L pail depending on thickness of application.

Coverage rates vary according to substrate, application technique, wastage factors and substrate preparation.

Application Method:

Trowel

Dry Film Build:

2-5mm

Typical Data at 25°C and 50% Relative Humidity

Drying Time:	48-72 hours
Touch Dry:	2 hours (dependent on substrate and conditions)
Dry to Recoat:	24-48 hours

No of Coats:

2

Clean Up:

Water

Packaging Sizes:

15L

Water Resistance:

Low

Substrate Conditions

- Substrate must be installed as per manufacturer's specifications.
- Substrate must be clean and free of dust, dirt, oil, salt, mould or any other contamination.
- Substrates must not contain more than 15% moisture prior to the application.
- For full details on application for each substrate, refer to the Rockcote Natural Materials Systems Guide.

Rockcote Terra Luxe

Active From:

30 Jun 2026

Mixing

- Mix thoroughly to achieve a homogeneous blend, ensuring full activation of components and controlled aeration for consistent workability.

Application

- Check colour prior to use to ensure consistency.
- Where possible, use products from the same batch on single wall to maintain colour consistency.
- Apply evenly over properly prepared substrate slightly thicker than the aggregate size to obtain desired finish.
- Terra Luxe is applied as a single coat, in two passes. First a tight coat, followed by a slightly thicker second pass to build to the required thickness.
- Directly after application, level with a wooden float then finish with a plastic float or steel trowel.
- The application of Rockcote Natural Materials is a highly skilled process that requires experience working with natural building products and systems. It is the responsibility of the applicator to select the right materials for the job and ensure correct installation and application according to the guidelines in the Rockcote Natural Materials Systems Guide and the attached specification. Rockcote strongly recommends that all Rockcote Natural Materials be applied by a licensed tradesperson who has extensive experience in applying the product for a similar application to the project at hand. Rockcote is not responsible for the ongoing maintenance of the Natural Material finishes, which is required in the upkeep and performance of the coating.

Precautions and Limitations

- Check colour before use.
- Internal use only
- Ensure same batch numbers are used on a single wall where possible.
- Should not be applied in temperatures below 5°C or above 35°C.
- Not suitable for areas of continual damp or areas submerged in water.

Transport and Storage

- Store in a cool dark place.
- Keep pail sealed.
- Do not stack over 3 high.

Disposal

- Dispose of in accordance with local council regulations

Safety Data

Refer to: Rockcote Terra Luxe Safety Data Sheet

Item Number

7498

Disclaimer

Rockcote Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, Rockcote Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.