TECHNICAL DATA SHEET

Rockcote Venetian Plaster

Active From: 07 Sep 2026



Rockcote Venetian Plaster is a traditional lime plaster developed for high gloss interior finish. This modern Venetian Plaster system that is durable whilst remaining sleek, elegant and high fashion mirror finish.

Features

- Can be polished to a mirror or glass finish
- Provides the illusion of depth in a polished finish
- Light-weight material: a marble look finish can be achieved in two coats
- Zero VOC
- Premixed product, just stir and apply to create a seamless finish
- Stunning aesthetics can be achieved by the creative artisan

Uses

- Venetian Plaster is ideal for crafting a polished cement render or polished concrete render industrial look.
- Venetian Plaster is especially useful for columns and walls where the appearance and feel of marble is sought and can achieve the light-reflective, lustrous properties of marble without the weight.
- Suitable for interior decorative finishes.
- Rockcote recommends ensuring clients sign off on samples to ensure all parties agree on aesthetics before the project begins, and all parties accept that aesthetics may change over time.

Colours and Gloss

- Natural white to off white.
- Can be tinted to various colours using paint tints or alkaline resistant oxides.
- Rockcote recommends not exceeding 4% of product weight in oxide addition.

Sheen Level: Glass

Coverage Rate: 60m2/15ltr

Approximately 60 square metres per 15 litre drum in 1 coat

Application Method: Venetian Stainless Steel Trowel

Dry Film Build: 0.5mm

Typical Data at 25^{o}C and 50% Relative Humidity

Drying Time: 4 hours

Touch Dry: 30 mins

Dry to Recoat: 4 hours

No of Coats: 2, but additional coats may be applied

Clean Up: Water

Packaging Sizes: 15L, 4L

Volume Solids: 50

Abrasion Resistance: Good

Rockcote Enterprises Pty Ltd
ABN 42 066 227 174
18 Machinery Rd, Yandina Q 4561
PO Box 230, Yandina Q 4561
Phone: 1300 736 668
Web: www.rockcote.com.au
Email: enquiries@rockcote.com.au
© Copyright 2026 Rockcote.
All rights reserved.

TECHNICAL DATA SHEET

Rockcote Venetian Plaster

Active From: 07 Sep 2026

Substrate Conditions

- Substrate must be installed as per manufacturer's specifications.
- Substrate must be clean and free of dust, dirt, oil, salt, mould or any other contamination.
- Any base coats should be fully cured.
- Substrates must not contain more than 15% moisture (WME) prior to the application of the Rockcote system.
- For full details on application for each substrate, refer to the Rockcote Natural Materials Systems Guide.

Mixing

Product in pail will consist of a lime putty with a protective water layer on top. Simply mix until consistent before applying.

Application

- Apply in a thin layer over surface and work with a steel trowel.
- Multiple coats can be applied for extra durability and protection.

Precautions and Limitations

- Check colour prior to use to ensure consistency. Where possible, use products from the same batch on single wall to maintain colour consistency.
- Rockcote Natural Materials range are manufactured using naturally occurring minerals and raw materials. As these materials are subject to natural variations in colour, composition and mineral characteristics, some variation in the finished colour may occur between production batches. Such variations are an inherent characteristic of natural mineral based products and are not considered a product defect.
- Where material from different production batches is required, appropriate boxing or mixing of batches should be undertaken to assist in achieving a more consistent overall appearance.
- Rockcote accepts no responsibility for colour variations that occur as a result of natural mineral or raw material variations.
- Rockcote Venetian Plaster is highly alkaline due to the inclusion of hydrated lime. Please ensure adequate PPE is used when mixing and applying.
- Many substrates can be coated with Rockcote Venetian Plaster but the high alkalinity may affect the underlying coating. Always contact Rockcote or refer to the Rockcote Natural Materials Systems Guide before using.
- Rockcote Venetian Plaster should not be applied in temperatures below 5°C or above 35°C.
- Rockcote Venetian Plaster is not suitable for areas of continual damp or areas submerged in water.
- Rockcote Venetian Plaster is not recommended for areas where water pools such as floors, shower floors, bath tubs or hand basins.
- The application of Rockcote Natural Materials is a highly skilled process that requires experience working with natural building products and systems. It is the responsibility of the applicator to select the right materials for the job and ensure correct installation and application according to the guidelines in the Rockcote Natural Materials Systems Guide and the attached specification. Rockcote strongly recommends that all Rockcote Natural Materials be applied by a licensed tradesperson who has extensive experience in applying the product for a similar application to the project at hand. Rockcote is not responsible for the ongoing maintenance of the Natural Material finishes, which is required in the upkeep and performance of the coating.

Transport and Storage

- Store in a cool, dark place.
- Do not stack over 3 high.
- Keep pail sealed.

Disposal

- Dispose of in accordance with local council regulations

Safety Data

Refer to Rockcote Venetian Plaster SDS.

Rockcote Enterprises Pty Ltd
ABN 42 066 227 174
18 Machinery Rd, Yandina Q 4561
PO Box 230, Yandina Q 4561
Phone: 1300 736 668
Web: www.rockcote.com.au
Email: enquiries@rockcote.com.au
© Copyright 2026 Rockcote.
All rights reserved.

TECHNICAL DATA SHEET

Rockcote Venetian Plaster

Active From: 07 Sep 2026

Item Number

4221, 4210

Disclaimer

Rockcote Enterprises Pty Ltd will not accept responsibility for any misuse of this product or if not applied by a skilled and experienced applicator and in accordance with our technical specifications. Due to our policy of continuing product improvement, Rockcote Enterprises Pty Ltd reserves the right to change these specifications without further notice. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

Rockcote Enterprises Pty Ltd
ABN 42 066 227 174
18 Machinery Rd, Yandina Q 4561
PO Box 230, Yandina Q 4561
Phone: 1300 736 668
Web: www.rockcote.com.au
Email: enquiries@rockcote.com.au
© Copyright 2026 Rockcote.
All rights reserved.